

Printing date 28.11.2023 Version number 9 (replaces version 8) Revision: 28.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Filter-Count
- · Article number: 6013149, 6013141
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Laboratory chemicals
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Revvity Health Sciences B.V.

Rigaweg 22

9723 TH Groningen

The Netherlands

Phone: 0031 50 5445900

www.revvity.com

· Further information obtainable from:

Quality Assurance, Environment, Safety & Health (QA/ESH)

SDS. Groningen@revvity.com

· 1.4 Emergency telephone number:

+31 50 5445971

CHEMTREC: +1 703-527-3887

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Eye Dam. 1 H318 Causes serious eye damage.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2

H315 Causes skin irritation.

STOT SE 3

H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Version number 9 (replaces version 8) Revision: 28.11.2023 Printing date 28.11.2023

Trade name: Filter-Count

(Contd. of page 1)

· Hazard pictograms









GHS05

GHS07

· Signal word Danger

Hazard-determining components of labelling:

1,2,4-trimethylbenzene

Sodium dioctyl sulphosuccinate

Alkylphenol polyglycolether

Nonylphenyl (branched) polyoxyethylene ether phosphate

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture: consisting of the following components.

CAS: 95-63-6	1,2,4-trimethylbenzene	60-80%
		00-00%
EINECS: 202-436-9	♦ Flam. Liq. 3, H226	
Index number: 601-043-00-3	Aquatic Chronic 2, H411	
	Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;	
	STOT SE 3, H335	
CAS: 78-40-0	Triethyl phosphate	10-20%
EINECS: 201-114-5	1 Acute Tox. 4, H302; Eye Irrit. 2, H319	
	Acute 10x. 4, 11502, Eye 111tt. 2, 11519	
Index number: 015-013-00-7		

(Contd. on page 3)



Printing date 28.11.2023 Version number 9 (replaces version 8) Revision: 28.11.2023

Trade name: Filter-Count

		(Contd. of page
CAS: 577-11-7 EINECS: 209-406-4	Sodium dioctyl sulphosuccinate Eye Dam. 1, H318 Skin Irrit. 2, H315	2.5-109
CAS: 9016-45-9 Polymer	Alkylphenol polyglycolether Eye Dam. 1, H318 Acute Tox. 4, H302 Aquatic Chronic 3, H412	
CAS: 68412-53-3 EINECS: 231-633-2	Nonylphenyl (branched) polyoxyethylene ether phosphate Eye Dam. 1, H318 Aquatic Chronic 2, H411 Skin Irrit. 2, H315	0-2.5%
CAS: 111-42-2 EINECS: 203-868-0 Index number: 603-071-00-1	2,2'-iminodiethanol Repr. 2, H361fd; STOT RE 2, H373 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315 Aquatic Chronic 3, H412	0-1%
· Non-dangerous components		
CAS: 92-71-7 2,5-Dipl EINECS: 202-181-3	henyloxazole (PPO)	0-2.59
CAS: 7732-18-5 water, d. EINECS: 231-791-2	istilled, conductivity or of similar purity	0-2.59
CAS: 13280-61-0 1,4-Bis-(EINECS: 236-285-5	(2-methylstyryl)-benzene (bis-MSB)	0-2.59

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed Headache
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

Fire-extinguishing powder

(Contd. on page 4)



Printing date 28.11.2023 Version number 9 (replaces version 8) Revision: 28.11.2023

Trade name: Filter-Count

(Contd. of page 3)

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow to enter sewers/surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

95-63-6 1,2,4-trimethylbenzene

WEL Long-term value: 125 mg/m³, 25 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 5)



Version number 9 (replaces version 8) Revision: 28.11.2023 Printing date 28.11.2023

Trade name: Filter-Count

(Contd. of page 4)

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

EN ISO 374-1/Type B

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.2 mm

Breakthrough time: > 120 minutes

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- **General Information**

Colour: Colourless Odour: Aromatic

· Boiling point or initial boiling point and boiling

170 °C (338 °F)

· Lower and upper explosion limit

· Lower: 1.1 Vol % (95-63-6 1,2,4-trimethylbenzene) · Upper: 7.0 Vol % Flash point: 50 °C (122 °F)

Auto-ignition temperature: 520 °C (968 °F)

·Solubility

Not miscible or difficult to mix. · water:

Density and/or relative density

Density at 20 °C (68 °F): 0.920 g/cm³ (7.6774 lbs/gal)

· 9.2 Other information

· Appearance:

Fluid · Form:

· Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

(Contd. on page 6)



Printing date 28.11.2023 Version number 9 (replaces version 8) Revision: 28.11.2023

Trade name: Filter-Count

		(Contd. of page 5)
Information with regard to physical hazard co	lasses	
· Explosives	Void	
· Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Flammable liquid and vapour.	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flamma	ble	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

ATE (Acute Toxicity Estimates)		
Oral	LD50	7,157 mg/kg
Inhalative	LC50/4 h	23.7 mg/l (Rat)
05 (2 (1 2 4 trim thall arrange		

95-63-6 1,.	95-63-6 1,2,4-trimethylbenzene	
Oral	LD50	3,400 mg/kg (Rat)
Dermal	LD50	3,160 mg/kg (Rabbit)
Inhalative	LC50/4 h	18 mg/l (Rat)

- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation

Causes serious eye damage.

- $\cdot \textit{Respiratory or skin sensitisation} \ \textit{Based on available data, the classification criteria are not met.}$
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 28.11.2023 Version number 9 (replaces version 8) Revision: 28.11.2023

Trade name: Filter-Count

(Contd. of page 6)

- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
95-63-6 1,.	,2,4-trimethylbenzene	
Inhalative	LC50	7.19-8.28 mg/l (Other fish)
	EC50/48h	6.14 mg/l (Daphnia magna)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA

1993

(Contd. on page 8)



Printing date 28.11.2023 Version number 9 (replaces version 8) Revision: 28.11.2023

Trade name: Filter-Count

(Contd. of page 7) · 14.2 UN proper shipping name · IMDG, IATA FLAMMABLE LIQUID, N.O.S. (1,2,4-trimethylbenzene) · 14.3 Transport hazard class(es) $\cdot ADR$ · Class *3 Flammable liquids.* ·Label · IMDG, IATA 3 Flammable liquids. ·Label 3 · 14.4 Packing group · ADR, IMDG, IATA III· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): Symbol (fish and tree) · 14.6 Special precautions for user Warning: Flammable liquids. Hazard identification number (Kemler code): EMS Number: F-E,S-E· 14.7 Maritime transport in bulk according to IMO Not applicable. instruments · UN "Model Regulation": UN1993, FLAMMABLE LIQUID, N.O.S., 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

(Contd. on page 9)



Printing date 28.11.2023 Version number 9 (replaces version 8) Revision: 28.11.2023

Trade name: Filter-Count

(Contd. of page 8)

- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- **Department issuing SDS:** Quality Assurance, Environment, Safety & Health (QA/ESH)
- · Contact: SDS.Groningen@revvity.com
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.