

Printing date 03/28/2024

Reviewed on 05/18/2023

1 Identification

- · Product identifier
- · Trade name: Toluene Radioactive LSC Standards
- · Product number:

6008400, 6008401A, 6008402A, 6008403A, 6008411A, 6008412A, 6008413A, 6008500A, 6008501A, 6008502A, 6008503A, 6008511A, 6008512A, 6008513A, 6018551A, 6018552A, 6018553A, 6018594A, 6018595A, 6018596A, 6018911A, 6018912A, 6018913A, 6018914A, 6018917A, 6018918A, 6018919A • Application of the substance / the mixture Laboratory chemicals

- Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Revvity, Inc 549 Albany Street Boston, MA 02118
- Information department: US Technical Support 800-762-4000
- *Emergency telephone number:* If inside USA, call CHEMTREC at 1-800-424-9300 If outside USA, call CHEMTREC at 1-703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture	
Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Skin Irritation 2	H315 Causes skin irritation.
Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity - Single Exposure 3	H336 May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to organs through prolonged or repeated exposure.
Aspiration Hazard 1 • Additional information: For the wording of the listed 1	H304 May be fatal if swallowed and enters airways. H phrases refer to section 16.
 Label elements GHS label elements The product is classified and labe Hazard pictograms 	led according to the Globally Harmonized System (GHS).
GHS02 GHS07 GHS08	
• Signal word Danger • Hazard-determining components of labeling:	
 GHS02 GHS07 GHS08 Signal word Danger Hazard-determining components of labeling: toluene 	
 GHS02 GHS07 GHS08 Signal word Danger Hazard-determining components of labeling: toluene Hazard statements 	
 GHS02 GHS07 GHS08 Signal word Danger Hazard-determining components of labeling: toluene 	
 GHS02 GHS07 GHS08 Signal word Danger Hazard-determining components of labeling: toluene Hazard statements Highly flammable liquid and vapor. 	
 GHS02 GHS07 GHS08 Signal word Danger Hazard-determining components of labeling: toluene Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. 	
 GHS02 GHS07 GHS08 Signal word Danger Hazard-determining components of labeling: toluene Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Suspected of damaging fertility or the unborn child. 	peated exposure.

75-100%

Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2024

Reviewed on 05/18/2023

Trade name: Toluene Radioactive LSC Standards

	(Contd. of page 1)
· Precautionary statements	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
Take off contaminated clothing and wash it before reuse.	
Dispose of contents/container in accordance with local/regional/national/international regulation	<i>S</i> .
· Classification system:	
· NFPA ratings (scale 0 - 4)	
$ \begin{array}{c} \textbf{Health} = 1 \\ Fire = 3 \\ Reactivity = 0 \end{array} $	

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

108-88-3 toluene

4 First-aid measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

(Contd. on page 3)

Printing date 03/28/2024

Reviewed on 05/18/2023

Trade name: Toluene Radioactive LSC Standards

(Contd. of page 2)

	utions, protective equipment and emergency procedures bry protective device.	
	equipment. Keep unprotected persons away.	
	<i>precautions:</i> Do not allow to enter sewers/ surface or ground water.	
	aterial for containment and cleaning up:	
	uid-binding material (sand, diatomite, acid binders, universal binders, sawdust,).
	inated material as waste according to section 13.	
Ensure adequate		
Reference to oth		
	r information on safe handling. r information on personal protection equipment	
See Section 8 for information on personal protection equipment.		
See Section 13 f	for disposal information	
	for disposal information. In Criteria for Chemicals	
Protective Actio	for disposal information. In Criteria for Chemicals	
	on Criteria for Chemicals	67 ppm
Protective Actio	on Criteria for Chemicals	
Protective Actio PAC-1: 108-88-3 92-71-7 2,5-di	on Criteria for Chemicals	
Protective Actio PAC-1: 108-88-3 92-71-7 2,5-di	on Criteria for Chemicals ne iphenyloxazole	
Protective Actio PAC-1: 108-88-3 92-71-7 2,5-di PAC-2:	on Criteria for Chemicals ne iphenyloxazole ne	2.5 mg/m ⁻ 560 ppm
Protective Actio PAC-1: 108-88-3 toluen 92-71-7 2,5-di PAC-2: 108-88-3 toluen 92-71-7 2,5-di	on Criteria for Chemicals ne iphenyloxazole ne	2.5 mg/m ⁻ 560 ppm
Protective Actio PAC-1: 108-88-3 toluen 92-71-7 2,5-di PAC-2: 108-88-3 108-88-3 toluen	on Criteria for Chemicals ne iphenyloxazole ne iphenyloxazole	2.5 mg/m ²

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and containers:* Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Storage class: 3
- Specific end use(s) No further relevant information available.

(Contd. on page 4)

Printing date 03/28/2024

Reviewed on 05/18/2023

Trade name: Toluene Radioactive LSC Standards

(Contd. of page 3)

	atrol parameters
	nponents with limit values that require monitoring at the workplace:
	-88-3 toluene (75-100%)
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	L Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm
TLV	⁷ Long-term value: 20 ppm BEI, OTO, A4
Ingr	redients with biological limit values:
108-	-88-3 toluene (75-100%)
BEI	0.02 mg/L
	Medium: blood
	Time: prior to last shift of workweek
	Parameter: Toluene
	0.03 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Toluene
	0.3 mg/g creatinine
	Medium: urine
	<i>Time: end of shift</i> <i>Parameter: o-Cresol with hydrolysis (background)</i>
	osure controls
	sonal protective equipment:
	neral protective and hygienic measures:
	p away from food and beverages. nediately remove all soiled and contaminated clothing.
	sh hands before breaks and at the end of work.
	e protective clothing separately.
	id contact with the skin.
	id contact with the eyes and skin.
	piratory protection:
	ase of brief or low exposure use an approved cartridge filter. In case of intensive or longer exposure u
SCB	
	able respiratory protective device recommended.
Prot	tection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (Contd. on page 5)

⁻ US

Printing date 03/28/2024

Reviewed on 05/18/2023

Trade name: Toluene Radioactive LSC Standards

· Material of gloves

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Appearance: Form:	Fluid
Form: Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	N/A
Change in condition	
Melting point/Melting range:	-95 °C (-139 °F)
Boiling point/Boiling range:	110 °C (230 °F)
Flash point:	4 °C (39.2 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	535 °C (995 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7 Vol %
Vapor pressure at 20 °C (68 °F):	29 hPa (21.8 mm Hg)
Vapor pressure at 50 °C (122 °F):	124 hPa (93 mm Hg)
Density at 20 °C (68 °F):	0.86564 g/cm ³ (7.22377 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water at 15 °C (59 °F):	0.5 g/l

— HS

Printing date 03/28/2024

Reviewed on 05/18/2023

Trade name: Toluene Radioactive LSC Standards

		(Contd. of page
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	99.3 %	
VOC content:	99.34 %	
Solids content:	0.7%	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

108-88-3 toluene

· NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.

(Contd. on page 7)

3

US

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2024

Reviewed on 05/18/2023

Trade name: Toluene Radioactive LSC Standards

• Ecotoxical effects: N/A

- Other information: N/A
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number ADR, IMDG, IATA	UN1294	
UN proper shipping name ADR IMDG, IATA	1294 TOLUENE mixture TOLUENE mixture	
Transport hazard class(es)		
ADR, IMDG, IATA		
Class Label	3 Flammable liquids 3	
Packing group ADR, IMDG, IATA	II	
Environmental hazards:	Not applicable.	
Special precautions for user Hazard identification number (Kemler co EMS Number: Stowage Category	Warning: Flammable liquids ode): 33 F-E,S-D B	
Transport in bulk according to Annex II MARPOL73/78 and the IBC Code	of Not applicable.	
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L	

Printing date 03/28/2024

Reviewed on 05/18/2023

Trade name: Toluene Radioactive LSC Standards

(Contd. of page 2
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
lL
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
UN 1294 TOLUENE MIXTURE, 3, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

Section 355 (extremely hazardous substances):			
None of the ingredients is listed.			
Section 313 (Specific toxic chemical listings):			
108-88-3 toluene			
· TSCA (Toxic Substances Control Act):			
108-88-3 toluene	ACTIVE		
92-71-7 2,5-diphenyloxazole	ACTIVE		
3073-87-8 1,4-bis(4-methyl-5-phenyloxazol-2-yl)benzene	ACTIVE		
· Hazardous Air Pollutants			
108-88-3 toluene			
· Proposition 65			
· Chemicals known to cause cancer:			
Radionuclide			
· Chemicals known to cause reproductive toxicity for females:			
None of the ingredients is listed.			
· Chemicals known to cause reproductive toxicity for males:			
None of the ingredients is listed.			
· Chemicals known to cause developmental toxicity:			
108-88-3 toluene			
· Carcinogenic categories			
· EPA (Environmental Protection Agency)			
108-88-3 toluene	II		
· TLV (Threshold Limit Value)			
108-88-3 toluene	A4		

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 9)

[–] US

Printing date 03/28/2024

Reviewed on 05/18/2023

Trade name: Toluene Radioactive LSC Standards

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 8)

16 Other information

The information provided in this safety data sheet is based on our current knowledge, and is believed to be correct at the date of publication. However, no representation is made concerning its accuracy and completeness. It is intended as guidance only, and is not to be regarded as a warranty or specification of quality. All materials may present unknown hazards and should be used with caution. Although certain hazards are described, we cannot guarantee that these are the only hazards that exist. Revvity, Inc. cannot be held liable for any damage resulting from handling or contact with the product.

· Contact:

• Date of preparation / last revision 03/28/2024 · Abbreviations and acronvms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation – Category 2 Toxic to Reproduction 2: Reproductive toxicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2 Aspiration Hazard 1: Aspiration hazard – Category 1